



## KROSS 0W30 FULL SYNTHETIC

This is a full synthetic lubricant based on carefully selected very high quality base oils. This oil is specifically formulated to meet both the BMW Longlife-12 FE and the Ford WSS M2C950-A specification. It is adapted to meet the requirements of the latest technology, highly engineered turbo engines requiring high performance and lower viscosity oils.

### APPLICATIONS

This product is mandatory in the newest BMW and Ford gasoline and diesel engines. It provides a multi vehicle application through the ACEA C2 specification. Optimum formulation for today's cars with exceptional film strength preventing oil film breakdown and reducing friction providing fuel economy and reliability.

### FEATURES

**Total engine protection:** Performance in keeping the engine clean.

**Fuel economy:** Superior fuel economy and CO2 reduction.

**Cold start:** Excellent fluidity at low temperature.

### MEETS OR EXCEEDS

ACEA C2 API SN Plus API SP ILSAC GF-5 BMW LONGLIFE-12 FE DAIMLER TRUCK DTFR 15D100 FIAT 9.55535-DS1 FIAT 9.55535-GS1 FORD WSS-M2C950-A JAGUAR-LAND ROVER STJLR.03.5007 MB 227.61 MB 229.61 OPEL OV 040 1547 - G30 VW 530 35.

The product has been blended to meet the above performance levels.

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average Results
Density at 15°C	ASTM D4052	g/ml	0.843
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	48.3
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	9.8
Viscosity index	ASTM D2270		194
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	9.4
Pour point	ASTM D6892	°C	-48
Flash Point COC	ASTM D92	°C	224

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### SIZES & PACKAGING

