



KROSS 0W20 FULL SYNTHETIC DPF

This is a full synthetic lubricant mandatory for the newest engines requiring ACEA C6. It is developed to prolong the life and maintain the efficiency of emission systems. It is also designed to provide outstanding engine cleanliness, wear protection and strong durability to keep your engine running like new.

APPLICATIONS

This product has been specifically developed to meet the challenging requirements of the latest C6 standard (can be used where ACEA C5 is recommended). A standard where protection against LSPI, offering fuel economy and CO2 reduction are important. Its also designed to meet the newest FORD WWSM2C952-A1 specification which is needed for the recent FORD Ecoblue engines (diesel).

FEATURES

Fuel economy: Superior fuel economy and CO2 reduction.

Cold start: Excellent fluidity at low temperature.

Aftertreatment protection: Full aftertreatment device protection.

MEETS OR EXCEEDS

ACEA C5 ACEA C6 API SN Plus API SP ILSAC GF-6 A FORD WSS-M2C952-A1 GM DexosD™ JAGUAR-LAND ROVER STJLR.03.5006 MB 229.71 OPEL OV 040 1547 - A20.

The product has been blended to meet the above performance levels.

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average Results
Density at 15°C	ASTM D4052	g/ml	0.843
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	39.8
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	8.3
Viscosity index	ASTM D2270		191
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	9.4
Pour point	ASTM D6892	°C	-45
Flash Point COC	ASTM D92	°C	234

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

SIZES & PACKAGING

