



KROSS 422 10W30

Universal multigrade oil for engines, transmissions, wet brakes and hydraulic systems of agricultural tractors.

APPLICATIONS

This multigrade oil is advised for the lubrication of charged and uncharged diesel engines (TURBO), 4-stroke gasoline engines and LPG-engines. This oil is intended for the lubrication of gear boxes, differentials, final drives, power take-off, wet brakes and hydraulic systems of agricultural tractors and engines for offhighway equipment.

FEATURES

Anti-wear and oxidation stability: Proven protection of critical parts.

Cold start: Excellent fluidity at low temperature.

MEETS OR EXCEEDS

ACEA E3 API CG-4 API GL-4 API GL-5 (Low speed/high torque) API SF/CE DIN 51524 T3 HVLPD ALLISON C4 (Agriculture applic.) CASE MAT 3525 CASE MAT 3526 FORD ESN-M2C134 C/D FORD ESN-M2C159 B/C FORD FNH 82009201 JD J20C JD J27 MF M 1135 MF M 1139 MF M 1143 MF M 1144 MF M 1145 NH NH 030C NH NH 410B NH NH 420A ZF TE-ML 03A ZF TE-ML 05K ZF TE-ML 06A ZF TE-ML 06B ZF TE-ML 06C ZF TE-ML 07B ZF TE-ML 07D.

The product has been blended to meet the above performance levels.

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average Results
Density at 15°C	ASTM D4052	g/ml	0.860
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	75
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	11.4
Viscosity index	ASTM D2270		144
Pour point	ASTM D6892	°C	-36
CCS viscosity at -25°C	ASTM D5293	mPa.s	6700
Flash Point COC	ASTM D92	°C	216

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

SIZES & PACKAGING

