



KROSS 4T 15W40 SYNTHETIC

This engine oil is specifically adapted for the lubrication of modern 4-stroke gasoline engines. The special composition ensures a perfect operation of the equipment and an excellent protection against dirt and deposits.

APPLICATIONS

It is specifically formulated for the lubrication of the 4-stroke engines of garden and construction machines, lawn mowers and auxiliary engines. Through its multigrade character, it can be used all year round.

FEATURES

Total engine protection: Performance in keeping the engine clean.

MEETS OR EXCEEDS

ACEA E2-level ACEA A3/B4-98 API CF JASO MA2 API CF-4 API SJ.

The product has been blended to meet the above performance levels.

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average Results
Density at 15°C	ASTM D4052	g/ml	0.883
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	107
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	14.0
Viscosity index	ASTM D2270		132
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	6.1
Pour point	ASTM D6892	°C	-30
CCS viscosity at -20°C	ASTM D5293	mPa.s	6850
Sulfated Ash	ASTM D874	Mass %	1,0
Flash Point COC	ASTM D92	°C	228

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

SIZES & PACKAGING



1 LT



4 LT



5 LT



20 LT



60 LT



200 LT



1000 LT