



KROSS 4T 20W50

Thanks to its stable base oils and advanced additive package, this four-stroke motorcycle engine oil guarantees a smooth and stable ride. The balanced formula is developed to exactly suit the needs of motorcycle enthusiasts looking for optimal riding comfort. The lubricant's high viscosity at high temperatures ensures complete engine protection in hot riding conditions.

APPLICATIONS

This lubricant is developed for the engines, transmissions and wet clutches of four-stroke motorcycles. It is perfectly balanced to meet the requirements of several manufacturers.

FEATURES

Extended motorcycle lifespan thanks to the oil's protective properties.
Protects the original riding comfort.
Simpler fluid management thanks to the oil's broad applicability.

MEETS OR EXCEEDS

JASO MA2 API SL.

The product has been blended to meet the above performance levels.

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average Results
Density at 15°C	ASTM D4052	g/ml	0.885
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	158
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	18.0
Viscosity index	ASTM D2270		126
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	5.9
Pour point	ASTM D6892	°C	-36
Colour	VISUAL		BROWN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

SIZES & PACKAGING

