



KROSS 5W20 FULL SYNTHETIC

Thanks to its low viscosity and outstanding fluidity this oil significantly reduces wear and ensures fuel savings and lower CO2 emissions. Optimized additive package reduces soot and deposits and keeps the engine clean. It is suitable for hybrid cars when the OEM specifications are met.

APPLICATIONS

This product has been specifically developed to meet the challenging requirements of the latest ILSAC GF-6 A standard where fuel economy and CO2 reduction are important. It provides the performance needed for the most recent requirements for gasoline-fueled US and Asian passenger cars.

FEATURES

Total engine protection: Performance in keeping the engine clean.

Fuel economy: Superior fuel economy and CO2 reduction.

Cold start: Excellent fluidity at low temperature.

MEETS OR EXCEEDS

API SN Plus GM dexos1™ Gen 2 API SN/RC ILSAC GF-5 CHRYSLER MS 6395 ILSAC GF-6 A FIAT 9.55535-CR1 API SP FORD WSS-M2C945-A API SP/RC FORD WSS-M2C946-A FORD WSS-M2C962-A FORD WSS-M2C947-A.

The product has been blended to meet the above performance levels.

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average Results
Density at 15°C	ASTM D4052	g/ml	0.846
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	45.1
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	8.48
Viscosity index	ASTM D2270		168
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	8.5
Pour point	ASTM D6892	°C	-39
Flash Point COC	ASTM D92	°C	230

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

SIZES & PACKAGING

