



## KROSS 5W30 C2 FULL SYNTHETIC

This is a full synthetic lubricant based on carefully selected very high quality base oils. This high - performance engine oil with low viscosity is specifically developed to provide the highest fuel economy and lowest CO2 emissions.

### APPLICATIONS

Specifically recommended for Peugeot and Citroën gasoline and diesel engines equipped with diesel particulate filters. Most Japanese OEM's, including Toyota, Honda, Subaru and Nissan.

### FEATURES

**Aftertreatment protection:** Full aftertreatment system protection.

**Total engine protection:** Outstanding engine cleanliness and durability.

**Fuel economy:** Lower fuel consumption and CO2 emissions.

### MEETS OR EXCEEDS

ACEA C2 FIAT 9.55535-S1 API SN/CF PSA B71 2290-2014 ILSAC GF-5 RENAULT RN 0700.

The product has been blended to meet the above performance levels.

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average Results
Density at 15°C	ASTM D4052	g/ml	0.856
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	57.0
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	10.1
Viscosity index	ASTM D2270		167
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	7.5
Pour point	ASTM D6892	°C	-39
CCS viscosity at -30°C	ASTM D5293	mPa.s	5500
Sulfated Ash	ASTM D874	Mass %	0.79
Flash Point COC	ASTM D92	°C	232

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### SIZES & PACKAGING

