



## KROSS 5W30 C2/C3 FULL SYNTHETIC

This synthetic engine oil formulation guarantees a cleaner and better performing engine without lowering the oil drain interval. The broad applicability of this lubricant enables you to offer perfect maintenance to different vehicles of several major brands.

### APPLICATIONS

This engine oil can be used in systems with or without exhaust gas after-treatment where C2 or C3 engine oils are required. Furthermore, this engine oil has the Renault RN 17 specification level. This means that you can use this lubricant where RN0700 & RN0710 were previously required, enabling you to service several Dacia and Renault models with this engine oil.

### FEATURES

**Broad coverage:** Reduced lubricant costs.

**Significant friction reduction:** Improved fuel efficiency and lowered emissions.

**Excellent engine cleanliness:** Outstanding engine protection during the entire oil drain interval.

### MEETS OR EXCEEDS

ACEA C2 MB 226.52 ACEA C3 MB 229.31 API SN MB 229.51 BMW LONGLIFE-04 MB 229.52 FIAT 9.55535-S1 OPEL OV 040 1547 - D30 FIAT 9.55535-S3 OPEL GM-LL-A-025 FORD WSS-M2C917-A OPEL GM-LL-B-025 GM dexos2™ RENAULT RN17 Level VW 505 00 IVECO 18-1811 Classe SC1 VW 505 01.

The product has been blended to meet the above performance levels.

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average Results
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	70.9
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	12.0
Viscosity index	ASTM D2270		167
B.N. (HClO <sub>4</sub> method)	ASTM D2896	mg KOH/g	7.8
Pour point	ASTM D6892	°C	-45
Sulfated Ash	ASTM D874	Mass %	0.78

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### SIZES & PACKAGING

