



KROSS 5W30 FULL SYNTHETIC

Thanks to its low viscosity and outstanding fluidity this oil significantly reduces wear and ensures fuel savings and lower CO₂ emissions. Optimized additive package reduces soot and deposits and keeps the engine clean. It is suitable for hybrid cars when the OEM specifications are met.

APPLICATIONS

This product has been specifically developed to meet the challenging requirements of the latest GM Dexos1 Gen 3 specification and ILSAC GF-6 A standard where fuel economy and CO₂ reduction are important. It provides the performance needed for the most recent requirements for gasoline-fueled US and Asian passenger cars.

FEATURES

Total engine protection: Performance in keeping the engine clean.

Fuel economy: Superior fuel economy and CO₂ reduction.

Cold start: Excellent fluidity at low temperature.

MEETS OR EXCEEDS

ACEA A5/B5, MB 229.3, MB229.51/229.31, PORSCHE A40, RN0700/0710, VW 50400/50700, OPEL GM-LL-B-025 BMW LL-01/LL-04, Dexos1, FIAT 9.55535-G27G1, FORD WSSM2937/947/945, Lexus LFA Service Fill PSA PEUGEOT CITROEN B70 2296, Nissan GT-R, Chrysler MS-6395, ILSAC - GF-6 A, CHRYSLER - MS 13340.

The product has been blended to meet the above performance levels.

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average Results
Density at 15°C	ASTM D4052	g/ml	0.871
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	80.03
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	11.31
Viscosity index	ASTM D2270		131
T.B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	7.7
Pour point	ASTM D6892	°C	-42
Flash point (COC)	ASTM D92	°C	228

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

SIZES & PACKAGING

