



## KROSS 75W90 GL-5

This is a full synthetic lubricant based on carefully selected very high quality base oils, which can be used in a wide field of applications. Because of its special composition, it is particularly suited for synchronized gear boxes, as well as heavily loaded differentials.

### APPLICATIONS

This oil is recommended for all components of mechanical transmissions (gear boxes, transfer boxes, differentials, etc.) of trucks and four-wheel drive vehicles.

### FEATURES

**Frictional properties:** Very smooth gear shifting, no vibration.

**Anti-wear and oxidation stability:** Superior protection of critical parts.

**Extended oil life:** Excellent thermal and oxidation stability.

### MEETS OR EXCEEDS

MACK GO-J SAE J 2360 RENAULT B0032/3 Annex 3 MIL PRF-2105E SCANIA STO 1:0 MB 235.8 VOLVO 97312 ARVIN MERITOR 0-76-N API GL-4 IVECO MIL-PRF-2105E API GL-5 MAN 341 E-3 API MT-1 MAN 341 Z-2 ZF TE-ML 05B MAN 342 M-3 ZF TE-ML 07A ZF TE-ML 16F ZF TE-ML 12B ZF TE-ML 17B ZF TE-ML 08 ZF TE-ML 19C ZF TE-ML 12L ZF TE-ML 21B ZF TE-ML 12N MB 235.11 DAF GL5/MIL-PRF-2105E ZF TE-ML 02B.

The product has been blended to meet the above performance levels.

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average Results
Density at 15°C	ASTM D4052	g/ml	0.868
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	76.3
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	15.2
Viscosity index	ASTM D2270		203
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	45.000

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### SIZES & PACKAGING

