



KROSS 85W140 GL-5

This is an extreme-pressure lubricant for gear boxes, specifically formulated to satisfy the highest service conditions: high speed, shockloads and high torque at low speeds.

APPLICATIONS

Recommended for all hypoid transmissions and also suitable for spiral bevel gears, worm wheels and most transaxles.

FEATURES

Frictional properties: Easy gear shifting.
Anti-wear protection: Long transmission life.

MEETS OR EXCEEDS

API GL-5 ZF TE-ML 71B MIL MIL-L-2105 C ZF TE-ML 19B MIL MIL-L-2105 D ZF TE-ML 07A ZF TE-ML 05A ZF TE-ML 16B ZF TE-ML 12E ZF TE-ML 16C ZF TE-ML 16D.

The product has been blended to meet the above performance levels.

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average Results |
|------------------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.908 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 367 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 26.1 |
| Viscosity index | ASTM D2270 | | 95 |
| Pour point | ASTM D6892 | °C | -15 |
| Copper corrosion | ASTM D130 | | 1B |
| Flash Point COC | ASTM D92 | °C | 215 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

SIZES & PACKAGING

