



KROSS ATF CVT

This is a full synthetic lubricant based on carefully selected very high quality base oils, that has been designed to be used in most CVT gearboxes. It is suitable for continuously variable transmissions, using steel push-belts or chains. It offers outstanding anti-wear protection and stable friction characteristics.

APPLICATIONS

OEMs usually recommend specific CVT fluids for their transmissions. By carefully balancing base oils and advanced additives, it has become possible to formulate this fluid that meets the requirements of both European and Japanese CVT manufacturers. This product may not be used in some hybrid vehicles, requiring special fluids.

FEATURES

Anti-wear protection: Significantly extended transmission life.

Frictional properties: Very smooth gear shifting, no vibration.

Extended oil life: Excellent thermal and oxidation stability.

MEETS OR EXCEEDS

DAIHATSU AMIX CVTF DFE HYUNDAI SP-CVT1 DAIHATSU AMIX CVTF-DC FORD WSS-M2C933-A VW G 052 180 HONDA HCF-2/HMMF (No Start Clutch) VW G 052 516 KIA SP-CVT 1 RENAULT ELFMATIC MB 236.20/CVT28 FUJIIYUUKO i-CVTF FG FORD MERCON C VOLVO CVT 4959 MAZDA CVTF 3320 BMW EZL799/EZL799A PUNCH EZL799/EZL799A TOYOTA CVT FE MINI EZL799/EZL799A/CVT V1 GM CVTF GREEN 2/SATURN DEX-CVT DODGE NS-2/CVTF+4 TOYOTA TC JEEP NS-2/CVTF+4 MITSUBISHI CVTF J-1 SUBARU e-CVTF AUDI TL 52180 NISSAN NS-1/NS-2/NS-3/Matic W FORD WSS-M2C928-A SUZUKI CVTF 3320.

The product has been blended to meet the above performance levels.

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average Results
Density at 15°C	ASTM D4052	g/ml	0.844
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	32.9
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	7.1
Viscosity index	ASTM D2270		187
Pour point	ASTM D6892	°C	-54
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	10600
Flash Point COC	ASTM D92	°C	188
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

SIZES & PACKAGING

