



KROSS DOT 4

Brake fluid, intended for hydraulic brake systems. Its composition provides a high chemical stability, excellent resistance against residue formation, very good stability towards oxidation and is compatible with all materials present in the circuit.

APPLICATIONS

It is suitable for all hydraulic brake circuits where the manufacturer recommends a fluid, which meets the specifications mentioned below. It is also suitable for numerous steering and clutch systems and can be used from -60°C till 225°C.

FEATURES

Boiling point: High boiling point, safe braking.

Anti-corrosion properties: Complete brake system protection.

Elastomer compatibility: No leakage or fluid losses.

MEETS OR EXCEEDS

SAE J 1704 ISO 4925 Class 3&4 FMVSS 116 DOT3 SAE J 1703 FMVSS 116 DOT 4.

The product has been blended to meet the above performance levels.

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average Results
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	2.1
pH	ASTM D1287		8.5
Equilibrium Reflux Boiling Point (ERBP)	ASTM D1120	°C	263
Wet Equilibrium Reflux Boiling Point (WERBP)	ASTM D1120	°C	165
Density at 20°C	ASTM D4052	g/ml	1.040
Kinematic viscosity at -40°C	ASTM D445	mm ² /s	1351

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

SIZES & PACKAGING



500ML



1LT



5LT



20LT



60LT



200LT



1000LT