



KROSS ISO 68 HYDRAULIC OIL

A mineral oil, specifically designed to meet the requirements of most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anti-corrosion and anti-foam additives.

APPLICATIONS

This oil is specifically designed to satisfy the requirements of the manufacturers of hydraulic systems where the highest demands are made concerning high pressure, temperatures or speeds. It is recommended for the hydraulic systems of the following types: Vickers, Gerotor, Gresen, HPM, Denison, Cessna, Hydreco and Worthington. It is also suitable for the lubrication of workshop equipment, reducing gears, bearings, compressed air systems and air screw compressors.

FEATURES

Anti-wear and oxidation stability: Superior protection.

Anti-foam properties: Excellent anti-foam properties.

Temperature stability: Adequate viscosity stability.

MEETS OR EXCEEDS

AFNOR NF E 48-603 HM AFNOR NF E 48-690 AFNOR NF E 48-691 ASTM D6158 HL, HM BOSCH REXROTH RDE 90235 CHINESE STANDARD GB 11118.1L-HL,L-HM CINCINNATI MACHINE P-69 (ISO 68) DANIELI 0.000.001Rev.15 Typ 10/11 DENISON HF-0, HF-1, HF-2 DIN 51524 Part 2 EATON E-FDGN-TB002-E EATON Brochure 03-401-2010 EATON VICKERS I-286-S EATON VICKERS M-2950-S GM LS2 AW hyd.oil ISO 11158, HM ISO 6743-4, HM JCMAS HK P014 SAE MS1004 US STEEL 126 ZF TE-ML 07H.

The product has been blended to meet the above performance levels.

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average Results
Density at 15°C	ASTM D4052	g/ml	0.884
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	69
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	8.7
Viscosity index	ASTM D2270		97
Pour point	ASTM D6892	°C	-27
Flash Point COC	ASTM D92	°C	230

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

SIZES & PACKAGING

