



KROSS SAE-30

High quality oil, suitable for diesel engines (supercharged or naturally aspirated) and gasoline engines operating in cold climatic conditions.

APPLICATIONS

This oil is particularly recommended for fixed diesel engines, material for public works and mixed fleets of trucks and cars.

FEATURES

Total engine protection: Performance in keeping the engine clean.

MEETS OR EXCEEDS

ACEA ALLISON E2/E1 C4 MIL MIL-L-2104 E MIL MIL-L-46152 E API CF-4/SG MTU Oil Category 1 CATERPILLAR TO-2 ZF TE-ML 03A MAN 270 ZF TE-ML 04A MB 227.0 ZF TE-ML 04B MB 228.0 ZF TE-ML 07D.

The product has been blended to meet the above performance levels.

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average Results
Density at 15°C	ASTM D4052	g/ml	0.890
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	103
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	11.8
Viscosity index	ASTM D2270		103
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	7.0
Pour point	ASTM D6892	°C	-42
Sulfated Ash	ASTM D874	Mass %	0.88
Flash Point COC	ASTM D92	°C	235

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

SIZES & PACKAGING

