



## KROSS SAE-50

Monograde motor oil, primarily intended for diesel engines, with or without turbo. It combines the following characteristics: very high resistance against oxidation, good detergent and dispersant properties, a great ability to neutralize acids and a high lubricity.

### APPLICATIONS

This motor oil is particularly suitable for fixed diesel engines for power generation of heavy trucks, working in warm climatic conditions.

### FEATURES

**Total engine protection:** Engine protection and cleanliness.

### MEETS OR EXCEEDS

API CF-4/SG MIL L-2104 E MIL L-46152 E MB 227.0.

The product has been blended to meet the above performance levels.

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average Results
Density at 15°C	ASTM D4052	g/ml	0.901
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	199
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	19.8
Viscosity index	ASTM D2270		97
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	9.7
Pour point	ASTM D6892	°C	-18
Sulfated Ash	ASTM D874	Mass %	1.10
Flash Point COC	ASTM D92	°C	244

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### SIZES & PACKAGING

