



KROSS SILICONE SPRAY

Silicone Lubricant Spray is a transparent spray with lubricating and anti-adhesive characteristics based on high-grade silicone oil.

APPLICATION

Reduces friction and reduces wear on mechanical parts and is therefore suitable for light lubrication of metals, plastics and rubbers. Prevents dirt and grease deposits and is therefore ideally suited for rails. Creates a water-repellent layer and protects the electric wiring of cars, engines, lawn mowers, etc. from moisture. Gives plastics and rubber a glossy finish. Not to be used for brake drums and brake discs. Treated surfaces cannot be painted.

FEATURES

- Lubricates.
- Reduces friction and wear.
- Rust and corrosion-resistant.
- Water-repellent.
- Electric insulating.
- For in and outdoor use.
- Aerosol can be used in any angle (360°).

TECHNICAL PROPERTIES

| | |
|---|-------------------------------|
| Basis | Mixture based on silicone oil |
| Consistency | Liquid |
| Density | Ca. 0,74 g/ml |
| Viscosity (Brookfield) | 29 mPa.s |
| Acidity level | Neutral |
| Solubility in water | Not soluble |
| Volatile Organic Compounds (VOC) | 90 % |
| Temperature resistance** | -40 °C - 200 °C |
| Application temperature | 5 °C - 30 °C |
| Dielectric strength | 14 kv/mm at 20°C |
| Resistance | 4 x 10E15 Ohm/cm |

* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. ** This information relates to fully cured product

SIZES & PACKAGING

500ML