

KROSS МАСЛО SAE-50



Сезонное моторное масло для смазки бензиновых и дизельных двигателей легковые автомобили с турбонаддувом или без него. Это масло сочетает в себе хорошие моющие и диспергирующие свойства, а также низкую зольность.

ПРИМЕНЕНИЯ

Это моторное масло особенно подходит для стационарных дизельных двигателей тяжелых грузовиков, работающих в теплых климатических условиях.

ФУНКЦИИ

Полная защита двигателя: эффективность поддержания чистоты двигателя.

СООТВЕТСТВИЕ

API CF-4/SG MIL L-2104 E MIL L-46152 E MB 227.0

The product has been blended to meet the above performance levels.

СИМВОЛИЧЕСКИЕ ХАРАКТЕРИСТИКИ

Test	Method	Unit	Average Results
Density at 15°C	ASTM D4052	g/ml	0.901
Kinematic viscosity at 40°C	ASTM D445	mmf/s	199
Kinematic viscosity at 100°C	ASTM D445	mmf/s	19.8
Viscosity index	ASTM D2270		97
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	9.7
Pour point	ASTM D6892	°C	-18
Sulfated Ash	ASTM D874	Mass %	1.10
Flash Point COC	ASTM D92	°C	244

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

ОБЪЕМ И УПАКОВКА



KHUELL PETROKİMYA SAN. ve TİC. A.Ş.
Lisans No: 11Y6/5367-143126
Date: 29.11.2023
www.kross.com.tr



FUEL
EFFICIENCY



Kross[®]
Motor Oil