



## KROSS СИЛИКОНОВЫЙ СПРЕЙ

*KROSS СИЛИКОНОВЫЙ СПРЕЙ – прозрачный спрей со смазывающими и антиадгезионными свойствами на основе высококачественного силиконового масла.*

### ПРИМЕНЕНИЕ

*Уменьшает трение и уменьшает износ механических частей и, следовательно, подходит для легкой смазки металлов, пластмасса и резины. Предотвращает отложение грязи и жира и поэтому идеально подходит для кабельных каналов. Создает водоотталкивающий слой и защищает электропроводку автомобилей, двигателей, газонокосилок и т. д. от влаги. Придает пластику и резине глянцевый блеск. Нельзя использовать для тормозных барабанов и тормозных дисков. Обработанные поверхности не подлежат окраске.*

### ФУНКЦИИ

*Смазывает  
Уменьшает трение и износ  
Устойчивость к ржавчине и коррозии  
Водоотталкивающий  
Электроизоляционные  
Для внутреннего и наружного использования  
Аэрозоль можно использовать под любым углом (360°).*

### ХАРАКТЕРИСТИКИ

Basis	Mixture based on silicone oil
Consistency	Liquid
Density	Ca. 0,74 g/ml
Viscosity (Brookfield)	29 mPa.s
Acidity level (text)	Neutral
Solubility in water	Not soluble
Volatile Organic Compounds (VOC)	90 %
Temperature resistance**	-40 °C - 200 °C
Application temperature	5°C-30°C
Dielectric strength	14 kv/mm at 20°C
Resistance	4 x 10E15 Ohm/cm

\* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates.

\*\* This information relates to fully cured product.

### ОБЪЕМ И УПАКОВКА

